

AIRPORT MASTER RECORD

Data Source: https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/

PRINT DATE: 5/18/2026
AFD EFF 05/14/2026

> 1 ASSOC CITY: WENDOVER 4 STATE: UT LOC ID: ENV FAA SITE NR: 25333.*A
> 2 AIRPORT NAME: WENDOVER 5 COUNTY: TOOELE UT
> 3 CBD TO AIRPORT (NM): 01 SE 6 REGION/ADO: ANM/DEN 7 SECT AERO CHT: SALT LAKE CITY

GENERAL

10 OWNERSHIP: PUBLIC
> 11 OWNER: TOOELE COUNTY
> 12 ADDRESS: P.O. BOX 159
WENDOVER, UT 84083
> 13 PHONE NR: 435-843-3360
> 14 MANAGER: LISA DUNN
> 15 ADDRESS: P.O. BOX 159
WENDOVER, UT 84083
> 16 PHONE NR: 435-843-3360
> 17 ATTENDANCE SCHEDULE:

ALL ALL 0800-1800

SERVICES

70 FUEL: 100 A
71 AIRFRAME RPRS: MINOR
72 PWR PLANT RPRS: MINOR
73 BOTTLE OXYGEN:
74 BULK OXYGEN:
75 TSNT STORAGE: HGR
76 OTHER SERVICES:

OPERATIONS

Information on aircraft operations is available from FAA's Aviation System Performance Metrics <https://aspm.faa.gov>

FACILITIES

18 AIRPORT USE: PUBLIC
19 ARPT LAT: 40-43-07.4110N ESTIMATED
20 ARPT LONG: 114-01-43.2250W
21 ARPT ELEV: 4236.7 SURVEYED
22 ACREAGE: 1,960
> 23 RIGHT TRAFFIC: 08, 12
> 24 NON-COMM LANDING: NO
25 NPIAS/FED AGREEMENTS: NPY
> 26 FAR 139 INDEX: IV B U 04/2005

80 ARPT BCN: WG
81 ARPT LGT SKED : SEE RMK
BCN LGT SKED: SS-SR
82 UNICOM: 122.800
83 WIND INDICATOR: YES
84 SEGMENTED CIRCLE: YES
85 CONTROL TWR: NO
86 FSS: CEDAR CITY
87 FSS ON ARPT: NO
88 FSS PHONE NR:
89 TOLL FREE NR: 1-800-WX-BRIEF

RUNWAY DATA

> 30 RUNWAY INDENT:
> 31 LENGTH:
> 32 WIDTH:
> 33 SURF TYPE-COND:
> 34 SURF TREATMENT:
35 GROSS WT: S
36 (IN THSDS) D
37 2D
38 2D/2D2
> 39 PCN:

| | 08/26 | 12/30 |
|----------------------|--------|--------|
| > 30 RUNWAY INDENT: | 10,002 | 8,002 |
| > 31 LENGTH: | 150 | 100 |
| > 32 WIDTH: | ASPH-G | ASPH-F |
| > 33 SURF TYPE-COND: | GRVD | GRVD |
| > 34 SURF TREATMENT: | 75.0 | 75.0 |
| 35 GROSS WT: S | 140.0 | 140.0 |
| 36 (IN THSDS) D | 208.0 | 180.0 |
| 37 2D | | |
| 38 2D/2D2 | | |
| > 39 PCN: | | |

LIGHTING/APCH AIDS

> 40 EDGE INTENSITY:
> 42 RWY MARK TYPE-COND:
> 43 VGS: 44 THR COSSING HGT.:
45 VISUAL GLIDE ANGLE:
> 46 CNTRLN-TDZ:
> 47 RVR-RVV:
> 48 REIL: Y / Y
> 49 APCH LIGHTS:

| | MED | MED | | |
|--------------------------|-------------------|-------------------|-------|-------|
| > 40 EDGE INTENSITY: | PIR - G / PIR - G | NPI - G / NPI - G | - / - | - / - |
| > 42 RWY MARK TYPE-COND: | P4L / P4L | / P4L | / | / |
| > 43 VGS: | 40 / 50 | / 45 | / | / |
| 44 THR COSSING HGT.: | 3.00 / 3.00 | / 3.00 | / | / |
| 45 VISUAL GLIDE ANGLE: | - / - | - / - | - / - | - / - |
| > 46 CNTRLN-TDZ: | - / - | - / - | - / - | - / - |
| > 47 RVR-RVV: | Y / Y | Y / Y | / | / |
| > 48 REIL: | / | / | / | / |
| > 49 APCH LIGHTS: | / | / | / | / |

OBSTRUCTION DATA

50 FAR 77 CATEGORY
> 51 DISPLACED THR:
> 52 CTLG OBSTN:
> 53 OBSTN MARKED/LGTD:
> 54 HGT ABOVE RWY END:
> 55 DIST FROM RWY END:
> 56 CNTRLN OFFSET:
57 OBSTN CLNC SLOPE:
58 CLOSE-IN OBSTN:

| | C / C | B(V) / B(V) | | |
|-------------------------|-------------|-------------|---|---|
| 50 FAR 77 CATEGORY | / | / | / | / |
| > 51 DISPLACED THR: | / | / | / | / |
| > 52 CTLG OBSTN: | / | / | / | / |
| > 53 OBSTN MARKED/LGTD: | / | / | / | / |
| > 54 HGT ABOVE RWY END: | / | / | / | / |
| > 55 DIST FROM RWY END: | / | / | / | / |
| > 56 CNTRLN OFFSET: | / | / | / | / |
| 57 OBSTN CLNC SLOPE: | 50:1 / 50:1 | 50:1 / 50:1 | / | / |
| 58 CLOSE-IN OBSTN: | N / N | N / N | / | / |

DECLARED DISTANCES

> 60 TAKE OFF RUN AVBL (TORA):
> 61 TAKE OFF DIST AVBL (TODA):
> 62 ACLT STOP DIST AVBL (ASDA):
> 63 LNDG DIST AVBL (LDA):

| | 10,002 / 10,002 | 8,002 / 8,002 | | |
|----------------------------------|-----------------|---------------|---|---|
| > 60 TAKE OFF RUN AVBL (TORA): | 10,002 / 10,002 | 8,002 / 8,002 | / | / |
| > 61 TAKE OFF DIST AVBL (TODA): | 10,002 / 10,002 | 8,002 / 8,002 | / | / |
| > 62 ACLT STOP DIST AVBL (ASDA): | 10,002 / 10,002 | 8,002 / 8,002 | / | / |
| > 63 LNDG DIST AVBL (LDA): | 10,002 / 10,002 | 8,002 / 8,002 | / | / |

> 110 REMARKS

A 026 24 HR PPR FOR ACFT OPNS WITH MORE THAN 30 PAX CALL AMGR 775-778-1891 OR 801-520-1613. WHEN REQD ARPT WILL MNTN ARFF INDEX B.
A 039 RWY 08/26 PCR VALUE: 490/F/D/X/T
A 039 RWY 12/30 PCR VALUE: 560/F/D/X/T
A 081 ACTVT REIL RWY 08, 12, 26, 30; PAPI RWY 08, 26, 30; MIRL RWY 08/26 & 12/30 - CTAF.
A 110-001 COLD TEMPERATURE AIRPORT. ALTITUDE CORRECTION REQUIRED AT OR BELOW -12C.
A 110-002 ALL SFCS AVBL TO ACRS.

111 INSPECTOR: (F)

112 LAST INSP: 02/25/2026

113 LAST INFO REQ:

AIRPORT MASTER RECORD

Data Source: https://www.faa.gov/air_traffic/flight_info/aeronav/aero_data/

PRINT DATE: 5/18/2026
AFD EFF 05/14/2026